

F-24060-02

DIN RAIL POWER SUPPLY



Product Features

- Maximum Output Power: 70W.
- High efficiency, long life and high reliability.
- Protection: Input fuse/overload/over voltage/ short circuit.
- Multifunction LED indicators.
- 100% full load burn-it test.
- Din Rail Mounting.

Description

F-24060-02 is a din rail power supply module with 2 output channels, DC output 24-28V/2.5A, maximum output power 70W.

Technical Specifications

Model		F-24060-02
INPUT	Voltage Range	190 - 265VAC
	Frequency Range	50 - 60Hz
OUTPUT	Voltage (AC Mode)	24-28V ±2% (Adjustable)
	Rated Current	2.5A
	Rated Power (Max.)	70W
	Efficiency (Typ.)	>86%
	Ripple & Noise	<240mVp-p
	Output Channel	2 Channels
PROTECTION	Input	2A/ 250VAC fuse
	Overload	3A ±5%
		Hiccup mode, recovers automatically after fault condition is removed
		PSU shuts down until AC power is reconnected
Short Circuit	Hiccup mode, recovers automatically after fault condition is removed	
ENVIRONMENT	Temperature	Working: -20°C~45°C, Storage: -30°C~80°C
	Humidity	Working: 20-80%RH, Storage: 10-90%RH
LED INDICATOR	Green	ON - DC ok
BOX	Dimension(mm)	89.5x93x56, can pack with a 12V 7Ah Lead Acid battery externally